

DESCRIPTION

High quality cast film for trucks' canvas and curtains-siders decoration. High adaptability and elasticity, doesn't fear folding or rolling up.

COLORS 23 semi-gloss

TECHNICAL INFORMATION

FILM	P.V.C. Cast
THICKNESS FILM (WITHOUT ADHESIVE)	80 +/- 5 micron
LINER	Clay coated paper 1 side siliconised
RELEASE	70 +/- 20 cN/20mm
ADHESIVE	Permanent adhesive extremely high adhesiveness onto plasticized P.V.C.
GRAMMAGE	45 +/- 5 g/m2
PEEL 180° AFTER 24 H ON BANNER PVC AT 20°C (ISTR. OP. N° 7)	min. 2100 g/ 25 mm
SHRINKAGE (48 H AT 70°C ON STEEL)	< 0,2 mm
LIFE *	5 years outdoor (When properly processed and under vertical condition)
APPLICATION TEMPERATURE	Suggested between 10 and 20 °C
TEMPERATURE RESISTANCE	From -40°C to + 60°C adhered to PVC no variation
SEAWATER RESISTANCE (ISTR. OP. N° 14)*	Adhered to PVC no variation after 100 h at 20°C (Ist. Op. 14)
SHELF LIFE	1 year normal condition (20°C / 50% R.H.) suspended horizontally or vertically upright position in polytene bag.

* References made to outdoor durability is based on middle european conditions. Exposure to conditions of high temperature as in southern climatic regions or in high polluted areas or in high altitudes or high UV conditions will reduce the performance levels. The values and data given are based on tests we believe to be reliable, and are typical values which are intended only as a source of information and do not constitute a warranty or a guarantee. The minimum life and seawater values given only refer to the film. Purchasers must independently determine, before use, the suitability of this material for the specific purpose and under their own operating conditions. No salesman, representative or agent has authority to give any guarantee, warranty or make any representation contrary to these guidelines . guarantee, warranty or make any representation contrary to these guidelines .